



MACARON

Specification Sheet V00

Selected Collection


kendila

Project: Type: Date:
Specifier:

Experience the whimsical elegance of our Macaron Pendant Light, inspired by the delicate charm of macarons. These vibrant pendant lights illuminate your space with an array of colors, adding visual allure and a playful touch to your surroundings. Perfect for various interior styles, they create a unique and enchanting ambiance.



APPLICATION



Pendant Light

ELECTRICAL

Operating Voltage

110-120VAC

Ingress Protection

IP20

Operating Ambient Temperature

-20°C to 45°C

Storage Temperature

-20°C to 45°C at 50% Humidity

Power

- Macaron 35 - 24W
- Macaron 45 - 24W
- Macaron 60 - 40W

LIGHTING

Light Source

E26 - LED BULBE

Color Temperature CCT

27 30 40

Color Rendering Index CRI

>90


Luminous Flux

80 Lumens/Watts


Dimming

TRIAC


DIMENSIONS



Macaron - S
Diameter
13.75" (35cm)



Macaron - M
Diameter
17.75" (45cm)



Macaron - L
Diameter
23.6" (60cm)

HOW TO SPECIFY

SLC	MCR			
Collection	Product	Finish	Size	CCT & CRI

SLC Selected	MCR Macaron	BLA Black	35 35cm (13.75")	27KH 2700K, 90+CRI
		ORA Orange	45 45cm (17.75")	30KH 3000K, 90+CRI
		RED Cherry RED	60 60cm (23.6")	40KH 4000K, 90+CRI
		GRA Grey		

WARRANTY



IMPORTANT NOTES

Do not install the fixture when power is on. Before powering ON, make sure the wiring is correct.

Avoid changing or damaging the circuit or other components of the fixture.

Avoid twist and irregular bend during installation, which might cause non repairable defect.

Power is fed on one side only, do not feed power on both sides.

kendila

Specification Sheet V00 - Selected - The Macaron



sales@kendila.com



www.kendila.com



+1 514 999 8098