



Shadow

Specification Sheet V00

Project: Type: Date:
Specifier:

Shadow Pendant Lights, a captivating collection inspired by the subtle charm of shadows. Illuminate your surroundings with a dance of sophisticated hues, infusing your space with both visual intrigue and a touch of mystery.



APPLICATION



Pendant Light

ELECTRICAL

Operating Voltage

110-120VAC

Ingress Protection

IP65

Operating Ambient Temperature

-20°C to 45°C

Storage Temperature

-20°C to 45°C at 50% Humidity

LIGHTING

Light Source

E26 - LED BULBE - Black Mirror Head

Color Temperature CCT

27 30 40

Color Rendering Index CRI

>90


Luminous Flux

1200 Lumens

Dimming


TRIAC

SHAPES & DIMENSIONS



Shadow - D

Available in
12" (30cm), 16" (40cm)



Shadow - A

Available in
12.5" (32cm), 19" (48cm)




Shadow - R

Available in
13.75" (35cm), 17.75" (45cm)




Shadow - O

Available in
10.5" (27cm)




Shadow - N

Available in
10.5" (27cm), 13" (33cm), 16" (40cm)



Shadow - E

Available in
12.5" (32cm), 16.5" (42cm)



Shadow - K


Available in
6.7" (17cm), 7.9" (20cm)



Shadow - S

Available in
6.3" (16cm), 7.5" (19cm)

HOW TO SPECIFY



SLC

Selected

SHD

Shadow

D

Shape D

A

Shape D

R

Shape D

K

Shape D

O

Shape D

N

Shape D

E

Shape D

S

Shape D

XX

Requested
Size
Following
Shape

27KS

2700K,
80+CRI

30KS

3000K,
80+CRI

40KS

4000K,
80+CRI

WARRANTY



IMPORTANT NOTES

Do not install the fixture when power is on. Before powering ON, make sure the wiring is correct.

Avoid changing or damaging the circuit or other components of the fixture.

Avoid twist and irregular bend during installation, which might cause non repairable defect.

Power is fed on one side only, do not feed power on both sides.

kendila

Specification Sheet V00 - Selected - The Shadow



sales@kendila.com



www.kendila.com



+1 514 999 8098